

PWG VeneerBackings GmbH
Aichener Strasse 8
D-86877 Walkertshofen, Germany



Tel. +49 (0) 82 39 – 2 14
Fax +49 (0) 82 39 – 75 52
pwg@pwg-veneerbackings.de

www.pwg-veneerbackings.de

Technical Data Sheet Veneer Jointing Tape 23ST/55K

Veneer Jointing Tape 23ST/55K is a heat-activatable adhesive tape which consists of a high-grade nonwoven with one-side glue coating. The tape is used to joint veneer stripes to veneer rolls in special veneer jointing machines.

Nonwoven Carrier

The nonwoven carrier mainly consists of long-fibrous cellulose. Synthetic fibres as well as latex binder are admixed for increasing tearing resistance and flexibility.

Glue Coating

The glue coating is applied from a water-based system. In combination with sufficient press temperature and pressure it provides a very heat- and water-resistant glue bond.

Processing

The tape is processed in special veneer jointing machines without application of additional glue. Possible tolerances in veneer thickness can cause poor sticking at the thinner veneer parts. The following processing conditions base on our own experience. Please consider that all types of wood and machinery are different. Therefore it is absolutely necessary to carry out own tests.

pressing temperature 250°C
pressing time 1.0 to 2.0 seconds
moistening of tape with water is highly recommended

Main Applications

manufacture of veneer rolls for production of veneer edge banding and profile wrapping veneers
lengthways jointing of veneers in parquet combination

Product Properties

high heat resistance of glue bond
minimum thickness after pressing
tape can be sanded away easily in further processing
good tearing resistance
good bonding of nonwoven's back side to various kinds of glue
different colors available

Physical Properties

thickness before pressing approx. 130 µm (5.1 mil)
tensile strength longitudinal 2.060 N/m
tensile strength lateral 1.410 N/m

Storage

temperature cool storage, by short-term up to 50°C
humidity dry storage, protect against water and humidity
shelf life minimum 6 months

Form of Delivery

packing in cardboard boxes on pallets
roll length 400 l.m. (1.310')
standard widths 42 mm (1.65") and 20 mm (0.78"); other widths on inquiry
quantity per box 10 rolls in 42 mm width or 21 rolls in 20 mm width
inside diameter 76 mm (3")

All information in the data sheet as well as our processing recommendations, irrespective whether given orally or in writing, are based on our own practical and scientific experience. These are given without obligation and therefore not a guarantee for any properties. Due to the multitude of materials and different processing conditions it is obligatory to clarify prior to the begin of the processing by examinations, suitable in extent and method, whether the product is suitable for the intended purpose. 01/2020