

Technical Data Sheet Backing Fleece 30ST/30

Backing Fleece 30ST/30 is a high-grade nonwoven with one-side glue coating. The material is applied onto veneer in fleece laminators with application of additional glue onto the veneer.

Nonwoven Carrier

The nonwoven carrier mainly consists of long-fibrous cellulose. Synthetic fibres as well as latex binder are admixed for increasing tearing resistance and flexibility.

Glue Coating

The glue coating is applied from a water-based system. In combination with a suitable lamination glue on the veneer it provides an excellent bond between fleece and veneer.

Processing

Backing Fleece 30ST/30 is processed in fleece laminators with application of lamination glue onto the veneer. Sufficient quantity and drying of the lamination glue is essential for a good bond between fleece and veneer. Please consider that all types of wood, machinery and lamination glue are different. Therefore it is absolutely necessary to carry out own tests.

Main Applications

manufacture of profile wrapping veneers
production of veneer edge banding

Product Properties

high reinforcement at high flexibility
high internal resistance of the carrier material, no splitting
increased productivity due to high lamination speed
good bonding of nonwoven's back side to various kinds of glue
different colors and all widths available

Physical Properties

weight	approx. 60 g/m ²
thickness	approx. 130 µm (5.1 mil)
tensile strength longitudinal	2.460 N/m
tensile strength lateral	1.510 N/m

Storage

temperature	cool storage, by short-term up to 50°C
humidity	dry storage, protect against water and humidity
shelf life	minimum 12 months

Form of Delivery

packing	rolls on pallets
roll length	1.500 l.m. (4.920')
available widths	50 mm (2.0") to 1.515 mm (59.6") in 5mm steps
inside diameter	76 mm (3")